



T-BAT SYS-HV

- Systematic design, in-depth optimization and seamless connection with Solax Hybrid inverter
- Safest type of LifePO₄ battery, an adoption of high-performance processors, international brand devices, better stability
- Long life cycle, more than 6000 times
- Safety Cert. TUV, CE, UL, UN38.3 and so on
- Remote fault diagnosis, upgrade and maintenance
- Auto power replenishment technology is adopted to prevent battery over-discharge
- Multiple communication interfaces :RS485, CAN
- Parallel function for expansion, with maximum of 8 pcs
- Floor or wall mounting
- IP55, supporting indoor and outdoor installation



T-BAT H 5.8



HV11550

	T-BAT H 5.8	T-BAT H 11.5	T-BAT H 17.3	T-BAT H 23
Nominal Voltage [V]	115.2	230.4	345.6	460.8
Operating Voltage [V]	100-131	200-262	300-393	400-524
Battery Type	Li-Ion (LFP)	Li-Ion (LFP)	Li-Ion (LFP)	Li-Ion (LFP)
Total Capacity [kWh]	5.8	11.5	17.3	23.0
Usable Capacity ¹⁾ [kWh]	5.1	10.4	15.5	20.7
Faradic Charge Efficiency [%]	99	99	99	99
Battery Roundtrip Efficiency [%]	95	95	95	95
Standard Power [kW]	2.8	5.7	8.6	11.5
Max Power [kW]	4.0	8.0	12.0	16.1
Recommend Charge/Discharge Current [A]	25	25	25	25
Max Charge/Discharge Current [A]	35	35	35	35
Short Circuit Current[A]	760	760	760	760
Cycle Life	>6000 Cycles	>6000 Cycles	>6000 Cycles	>6000 Cycles
Warranty [Year]	10	10	10	10
Available Operating Temperature Range [°C]	0 to 55			
Full-load Operating Temperature Range [°C]	5 to 48			
Relative Humidity [%]	4 to 100 (condensing)			
Altitude [m]	Below 2000			
Protection	IP55			
System to Inverter	CAN2.0			
Battery to Battery/BMS	RS485			
Data Collection Port /FW UPDATE	CAN2.0			
Master Control Working Mode Indicator	1 LED			
Master Control Capacity Indicator	4LED (25%, 50%, 75%, 100%)			
Battery Module LED	2 LED			
Reset	Button			
Switch ON/OFF	Buttonx1 + breakerx1			
Safety	CE, RCM, IEC62619, UL1973, ROHS, REACH			
UN Number	UN3840			
Hazardous Materials Classification	Class 9			
Transport Testing Requirement	UN38.3			
Dimensions(LxWxH) [mm]	474x193x708	474x193x708+174x193x647	474x193x708+174x193x647x2	474x193x708+174x193x647x3
Weight [kg]	7.2	7.2+6.5	7.2+6.5x2	7.2+6.5x3

¹⁾ Test conditions:90% DOD, 0.2C charger & discharger @+25°C
 The Triple Power battery could be scalable up to 4 modules, for a total of 23.0kWh.
 Indoor installation only
 system Usable Energy may be variant, with different inverter models
 Max Charge/Discharge Current may be variant with different inverter models

V2.0*Information may be subject to change without notice. 650.0012.00